5Watt Single Output

CASE: P22-1

Features:

- AC to DC Module
- Smallest Size, Low Profile
- Protections: SCP/ OLP/ OVP
- EMI Fliter Inside
- 100% full load burn-in test

Input Volt. & Freq. ····· 176~264VAC (210~370VDC)

Inrush Current ····· 30A@230Vac (cold start)

DC adjustment range····· ±5%(rated output voltage)

Overload protection ····· 105%~150% (rated load), Auto-recovery

Over voltage protection ····· 115%~135%(rated output voltage)

Setup time ····· ····· ≤1S@230VAC

Hold-up time ····· ≥20mS@230VAC

Withstand voltage ····· Input-Output: AC1500V, 1min

Input-Ground: AC1500V, 1min

Output-Ground: DC500V, 1min

Operating ambient ····· 0℃~50℃; 20%~90%RH (Non condensing)

Safety standards ····· EN/UL60950

EMC standards····· EN55022 Class B;

EN61000-4-2/-3/-4/-5/-6/-11

Dimension(L*W*H) ····· 55×45×18mm

Model No.	DC Output		Tol.	R&N	Effi.
PMA-H5S5	5V	1A	±3%	≤50mV	76%
PMA-H5S12	12V	0. 4A	±3%	≤120mV	78%