


20W Single Output Switching Power Supply



CASE: P56-5

Features:

- Miniature & thin
- AC input 176-264V only
- Protections: SCP/ OLP/ OVP
- High reliability, Low cost
- 100% full load burn-in test

input Volt. & Freq.	176~264VAC/47~63Hz
Inrush Current.....	40A@230VAC (cold start)
DC adjustment range	±10% (rated output voltage)
Overload protection	105%~280% (rated load)
Over voltage protection.....	115%~150% (rated output voltage)
Short circuit protection.....	Long-term
Setup time	≤1S@230VAC
Hold-up time	≥20mS@230VAC
Withstand voltage.....	Input-Output: AC1500V, 1min
	Input-Ground: AC1500V, 1min
	Output-Ground: DC500V, 1min
Operating ambient.....	-20~45°C, 20%~90%RH (Non condensing)
Safety standards.....	EN60950, GB4943
Dimension (L*W*H)	115X49X27 mm

Model No.	DC Output		Tol.	R&N	Effi.
LPC-H20S5	5V	4A	±3%	≤50mV	75%
LPC-H20S12	12V	2A	±3%	≤120mV	78%
LPC-H20S15	15V	1.4A	±3%	≤150mV	78%
LPC-H20S24	24V	0.8A	±3%	≤240mV	78%