

25W Single Output Switching Power Supply



CASE: P52-2

Features:

- Normal Size
- AC input 176-264V only
- Protections: SCP/ OLP/ OVP
- High reliability, Low cost
- 100% full load burn-in test

Input Volt. & Freq.	176~264VAC/47~63Hz
Inrush Current.....	40A@230VAC (cold start)
DC adjustment range	±10% (rated output voltage)
Overload protection	105%~150% (rated load), Auto-recovery
Over voltage protection.....	115%~135% (rated output voltage)
Short circuit protection.....	Long-term
Setup time	≤1S@230VAC
Hold-up time	≥20mS@230VAC
Withstand voltage.....	Input-Output: AC1500V, 1min
	Input-Ground: AC1500V, 1min
	Output-Ground: DC500V, 1min
Operating ambient.....	0~45°C, 20%~90%RH (Non condensing)
Safety standards.....	EN60950, GB4943
Dimension (L*W*H)	143X59X38 mm

Model No.	DC Output	Tol.	R&N	Effi.
GZM-H25S5	5V 5A	±3%	≤50mV	71%
GZM-H25S8.5	8.5V 3A	±3%	≤85mV	65%
GZM-H25S12	12V 2.1A	±3%	≤120mV	75%
GZM-H25S15	15V 1.7A	±3%	≤150mV	75%
GZM-H25S24	24V 1.1A	±3%	≤240mV	78%