45W Dual Output Switching Power Supply

Features:

- Normal Size
- AC input 176-264V only
- Protections:SCP/ OLP/ OVP
- High reliablity, Low cost
- 100% full load burn-in test

Input Volt. & Freq. ·····176~264VAC/47~63Hz

Inrush Current·····40A@230VAC (cold start)

DC adjustment range ····· ±10% (rated output voltage)

Overload protection ·····105%~150% (rated load), Auto-recovery

Over voltage protection·····115%~135% (rated output voltage)

Short circuit protection····· Long-term

Setup time ····· ≤1S@230VAC

Hold-up time ····· ≥20mS@230VAC

Withstand voltage·····Input-Output: AC1500V, 1min

Input-Ground: AC1500V, 1min

Output-Ground: DC500V, 1min

Operating ambient·····0~45℃,20%~90%RH (Non condensing)

Safety standards·····EN60950,GB4943

Dimension (L*W*H) ·····129X98X38 mm

Model No.	DC Output		Tol.	R&N	Effi.
GZM-H45D5+15	5V	3A	±1%	≤50mV	65%
	15V	2A	±3%	≤150mV	
GZM-H45D5+12I	5V	3A	±3%	≤50mV	70%
	12V	2.5A	±3%	≤120mV	
GZM-H45D5+24	5V	2A	±3%	≤50mV	70%
	24V	1.5A	±3%	≤240mV	
GZM-H45D24+5	24V	2A	±3%	≤240mV	70%
	5V	1A	±3%	≤50mV	
GZM-H45D12-12	12V	2A	±3%	≤120mV	70%
	-12V	2A	±3%	≤120mV	