

60W Dual Output Switching Power Supply



Features:

- Miniature
- AC input 176-264V only
- Protections : SCP/ OLP/ OVP
- High reliability, Low cost
- 100% full load burn-in test

Input Volt. & Freq.	176~264VAC/47~63Hz (210~370VDC)
Inrush Current	40A@230Vac (cold start)
DC adjustment range.....	± 10%(rated output voltage)
Overload protection	130%~150% (rated load), Auto-recovery
Over voltage protection	105%~135%(rated output voltage)
Short circuit protection.....	Long-term
Setup time	≤1.5S@230VAC
Hold-up time	≥20mS@230VAC
Withstand voltage	Input-Output: AC3000V, 1min
	Input-Ground: AC1500V, 1min
	Output-Ground: DC500V, 1min
Operating ambient	0°C~50°C; 20%~90%RH (Non condensing)
Safety standards	EN/UL60950
EMC standards.....	EN55022 Class B;
	EN61000-4-2/-3/-4/-5/-6/-11
Dimension(L*W*H)	127×76×40mm

Model No.	DC Output		Tol.	R&N	Effi.
MGZ-H60D3. 3+12	3.3V	10A	≤±3%	≤50mV	68%
	12V	1A	≤±10%	≤120mV	
MGZ-H60D5+12	5V	10A	≤±3%	≤500mV	75%
	12V	1A	≤±10%	≤120mV	