

Features:

- High reliability, low cost
 - Built-in EMI filter
- 100% full load burn-in test
 Protections: overload/ short circuit
 2 year warranty



Product Name		PDF 100-12	PDF 100-24
Output	DC Voltage	12V	24V
	Rated Current	8.33A	4.16A
	Current Range	0-8.33A	0-4.16A
	Rated Power	100W	100W
	Ripple&Roise	80mVp-p	80mVp-p
	Dimmable ways	Triac ,0-10V,1-10V,PWM Signal	Triac ,0-10V,1-10V,PWM Signal
input	Voltage Range	170-260VAC	170-260VAC
	Frequency Range	47-63HZ	47-63HZ
	Efficiency	85%	85%
	Leakage Current	≤5MA 230VAC	≤5MA 230VAC
Protection	Overload	110-150% Rated output power	110-150% Rated output power
		Protection type:Hiccup mode,recovers automatically after fault condition is removed	Protection type:Hiccup mode,recovers automatically after fault condition is removed
	Over Voltage	Protection type : Shut down o/p voltage, re-power on to recover	Protection type : Shut down o/p voltage, re-power on to recover
	Short Circuit	Auto recovery	Auto recovery
Environment	Working Temp.	-10℃-50℃	-10℃-50℃
	Working Humidity	20%-90%	20%-90%
	storage Temp.&Humidity	-20℃-85℃,10%-95%	-20℃-85℃,10%-95%
Approval Standards		CE ROHS	CE ROHS
Others	packing mode	White Box	White Box
	Product Dimemsion	230*50*30MM	230*50*30MM
	Box size	240*55*35MM	240*55*35MM
	Carton size	45*29*25.5CM	45*29*25.5CM
	Packing information	280g;60Pcs/CTN;19.5KG	280g;60Pcs/CTN;19.5KG