



Features:

- High reliability, low cost
 - Built-in EMI filter
- 100% full load burn-in test
 Protections: overload/ short circuit
 2 year warranty

Product Name		PDF 60-12	PDF 60-24
Output	DC Voltage	12V	24V
	Rated Current	5A	2.5A
	Current Range	0-5A	0-2.5A
	Rated Power	60W	60W
	Ripple&Roise	80mVp-p	80mVp-p
	Dimmable ways	Triac ,0-10V,1-10V,PWM Signal	Triac ,0-10V,1-10V,PWM Signal
input	Voltage Range	170-260VAC	170-260VAC
	Frequency Range	47-63HZ	47-63HZ
	Efficiency	85%	85%
	Leakage Current	≤5MA 230VAC	≤5MA 230VAC
Protection	Overload	110-150% Rated output power	110-150% Rated output power
		Protection type:Hiccup mode,recovers automatically after fault condition is removed	Protection type:Hiccup mode,recovers automatically after fault condition is removed
	Over Voltage	Protection type : Shut down o/p voltage, re-power on to recover	Protection type : Shut down o/p voltage, re-power on to recover
	Short Circuit	Auto recovery	Auto recovery
Environment	Working Temp.	-10℃-50℃	-10℃-50℃
	Working Humidity	20%-90%	20%-90%
	storage Temp.&Humidity	-20℃-85℃,10%-95%	-20℃-85℃,10%-95%
Approval Standards		CE ROHS	CE ROHS
Others	packing mode	White Box	White Box
	Product Dimemsion	187*50*30MM	187*50*30MM
	Box size	200*55*35MM	200*55*35MM
	Carton size	45*29*25.5CM	45*29*25.5CM
	Packing information	210g;60Pcs/CTN;14.8KG	210g;60Pcs/CTN;14.8KG