

15W Single Output Switching Power Supply



2

Features:

- Miniature
- AC input 176-264V only
- Protections : SCP/ OLP/ OVP
- High reliability, Low cost
- 100% full load burn-in test

Input Volt. & Freq.	176~264VAC/47~63Hz (210~370VDC)
Inrush Current	40A @ 230Vac (cold start)
DC adjustment range	± 10%(rated output voltage)
Overload protection	105%~150% (rated load), Auto-recovery
Over voltage protection	115%~135%(rated output voltage)
Short circuit protection	Long-term
Setup time	≤ 1S @ 230VAC
Hold-up time	≥ 20mS @ 230VAC
Withstand voltage	Input-Output: AC1500V, 1min Input-Ground: AC1500V, 1min Output-Ground: DC500V, 1min
Operating ambient	0°C~50°C; 20%~90%RH (Non condensing)
Safety standards	EN/UL60950
EMC standards	EN55022 Class B; EN61000-4-2/-3/-4/-5/-6/-11
Dimension(L*W*H)	100 × 55 × 27mm

Model No.	DC Output		Tol.	R&N	Effi.
GZM-H15S5	5V	3A	±3%	≤ 50mV	68%
GZM-H15S12	12V	1.25A	±3%	≤ 120mV	73%
GZM-H15S24	24V	0.83A	±3%	≤ 240mV	74%